Route du Pré-au-Comte 8 • CH-1844 Villeneuve • •41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model: Serial number: CONTRACT

PG_1941.2022

23.02.2022

Niviuk Gliders / Air Games S.L.

Koyot 5 22

OIKT4222V1

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	70	Range of speed system (cm)	14
Minimum weight in flight (kg)	45	Speed range using brakes (km/h)	15
Glider's weight (kg)	4.2	Total speed range with accessories (km/h)	21
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	18.75		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	every 24 months or every 100 flying hours	
Harness brand	Supair	Warning! Before use refer to user's manual	
Harness model	Altiplume S	Person or company having presented the glider for testing: NEF Olivier	
Harness to risers distance (cm)	44		
Distance between risers (cm)	40		

Route du Pré-au-Comte 8 • CH-1844 Villeneuve • •41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model: Serial number: CONTRACT

PG_1940.2022

23.02.2022

Niviuk Gliders / Air Games S.L.

Koyot 5 24

OIKT4242V1

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	80	Range of speed system (cm)	13
Minimum weight in flight (kg)	60	Speed range using brakes (km/h)	15
Glider's weight (kg)	4.6	Total speed range with accessories (km/h)	21
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	20.45		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	every 24 months or every 100 flying hours	
Harness brand	Advance	Warning! Before use refer to user's manual	
Harness model	Success 4	Person or company having presented the	
	М	glider for testing: None	
Harness to risers distance (cm)	44		
Distance between risers (cm)	40		

Route du Pré-au-Comte 8 • CH-1844 Villeneuve • •41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

CONTRACT

PG_1939.2022

23.02.2022

Niviuk Gliders / Air Games S.L.

Koyot 5 26

OIKT4262V1

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	95	Range of speed system (cm)	15
Minimum weight in flight (kg)	75	Speed range using brakes (km/h)	15
Glider's weight (kg)	4.8	Total speed range with accessories (km/h)	21
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	22.16		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	every 24 months or every 100 flying hours	
Harness brand	Supair	Warning! Before use refer to user's manual	
Harness model	Evo XC 3 L	Person or company having presented the glider for testing: None	
Harness to risers distance (cm)	44		
Distance between risers (cm)	44		

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23

Route du Pré-au-Comte 8 • CH-1844 Villeneuve • •41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

CONTRACT

PG_1938.2022

23.02.2022

Niviuk Gliders / Air Games S.L.

Koyot 5 28

OIKT4282V1

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	115	Range of speed system (cm)	13
Minimum weight in flight (kg)	90	Speed range using brakes (km/h)	15
Glider's weight (kg)	5.1	Total speed range with accessories (km/h)	21
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	23.86		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	every 24 months or every 100 flying hours	
Harness brand	Supair	Warning! Before use refer to user's manual	
Harness model	Evo XC 3 L	Person or company having presented the glider for testing: None	
Harness to risers distance (cm)	44		
Distance between risers (cm)	48		

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23

Route du Pré-au-Comte 8 • CH-1844 Villeneuve • •41 (0)2) 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

CONTRACT

PG_1937.2022

23.02.2022

Niviuk Gliders / Air Games S.L.

Koyot 5 31

OIKT4312V1

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	135	Range of speed system (cm)	13
Minimum weight in flight (kg)	110	Speed range using brakes (km/h)	15
Glider's weight (kg)	5.5	Total speed range with accessories (km/h)	21
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	26.42		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	every 24 months or every 100 flying hours	
Harness brand	Supair	Warning! Before use refer to user's manual	
Harness model	Evo XC 3 L	Person or company having presented the glider for testing: None	
Harness to risers distance (cm)	44		
Distance between risers (cm)	48		

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23