



Classification: **B**



In accordance with standards EN 926-1:2015, EN 926-2:2013+A1:2021 and NfL 2-565-20

PG_2045.2022

Date of issue (DMY):

27.09.2022

Manufacturer:

Niviuk Gliders / Air Games S.L.

Model:

Hook 6 P 20

Serial number:

HOOK6P201

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	70
Minimum weight in flight (kg)	55
Glider's weight (kg)	3.2
Number of risers	3+1
Projected area (m2)	17.15

Accessories

Range of speed system (cm)	13.7
Speed range using brakes (km/h)	14
Total speed range with accessories (km/h)	25
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Woody Valley
Harness model	Wani Light 2 M
Harness to risers distance (cm)	43
Distance between risers (cm)	40

Inspections (whichever happens first)

every 100 hours of use or every 24 months (whichever happens first)	
Warning! Before use refer to user's manual	
Person or company having presented the glider for testing: None	

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A A A A A A A A A A A A A B A A A A A A A 0

AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comté 8 ▲ CH-1844 Villeneuve ▲ +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses
and paraglider reserve parachutes



Classification: **A**

 **NIVIUK**

In accordance with standards EN 926-1:2015, EN 926-2:2013+A1:2021 and NfL 2-565-20

PG_2046.2022

Date of issue (DMY):

27.09.2022

Manufacturer:

Niviuk Gliders / Air Games S.L.

Model:

Hook 6 P 22

Serial number:

HOOK6P221

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	80
Minimum weight in flight (kg)	60
Glider's weight (kg)	3.4
Number of risers	3+1
Projected area (m2)	18.87

Accessories

Range of speed system (cm)	16.6
Speed range using brakes (km/h)	14
Total speed range with accessories (km/h)	25
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Advance
Harness model	Success 4 M
Harness to risers distance (cm)	43
Distance between risers (cm)	44

Inspections (whichever happens first)

every 100 hours of use or every 24 months (whichever happens first)
Warning! Before use refer to user's manual
Person or company having presented the glider for testing: **None**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0



Classification: **A**



In accordance with standards EN 926-1:2015, EN 926-2:2013+A1:2021 and NfL 2-565-20

PG_2043.2022

Date of issue (DMY):

27.09.2022

Manufacturer:

Niviuk Gliders / Air Games S.L.

Model:

Hook 6 P 24

Serial number:

HOOK6P241

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	92
Minimum weight in flight (kg)	70
Glider's weight (kg)	3.7
Number of risers	3+1
Projected area (m2)	20.59

Accessories

Range of speed system (cm)	16.7
Speed range using brakes (km/h)	14
Total speed range with accessories (km/h)	25
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Advance
Harness model	Success 4 M
Harness to risers distance (cm)	43
Distance between risers (cm)	44

Inspections (whichever happens first)

every 100 hours of use or every 24 months (whichever happens first)
Warning! Before use refer to user's manual
Person or company having presented the glider for testing: **None**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0



Classification: **A**



In accordance with standards EN 926-1:2015, EN 926-2:2013+A1:2021 and NfL 2-565-20

PG_2047.2022

Date of issue (DMY):

27.09.2022

Manufacturer:

Niviuk Gliders / Air Games S.L.

Model:

Hook 6 P 26

Serial number:

HOOK6P261

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	105
Minimum weight in flight (kg)	80
Glider's weight (kg)	4
Number of risers	3+1
Projected area (m2)	22.3

Accessories

Range of speed system (cm)	16.9
Speed range using brakes (km/h)	14
Total speed range with accessories (km/h)	25
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Dudek
Harness model	Zero Gravity M
Harness to risers distance (cm)	43
Distance between risers (cm)	46

Inspections (whichever happens first)

every 100 hours of use or every 24 months (whichever happens first)
Warning! Before use refer to user's manual
Person or company having presented the glider for testing: **None**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0

AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comté 8 ▲ CH-1844 Villeneuve ▲ +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses
and paraglider reserve parachutes



Classification: **A**



In accordance with standards EN 926-1:2015, EN 926-2:2013+A1:2021 and NfL 2-565-20

PG_2048.2022

Date of issue (DMY):

27.09.2022

Manufacturer:

Niviuk Gliders / Air Games S.L.

Model:

Hook 6 P 28

Serial number:

HOOK6P281

Configuration during flight tests

Paraglider

Maximum weight in flight (kg)	120
Minimum weight in flight (kg)	95
Glider's weight (kg)	4.3
Number of risers	3+1
Projected area (m2)	24.02

Accessories

Range of speed system (cm)	16.1
Speed range using brakes (km/h)	14
Total speed range with accessories (km/h)	25
Range of trimmers (cm)	0

Harness used for testing (max weight)

Harness type	ABS
Harness brand	Supair
Harness model	Evo XC 3 L
Harness to risers distance (cm)	44
Distance between risers (cm)	48

Inspections (whichever happens first)

every 100 hours of use or every 24 months (whichever happens first)
Warning! Before use refer to user's manual
Person or company having presented the glider for testing: **None**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
A 0