Route du Pré-au-Compte 8 * CH-1844 Villeneuve * +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes





Classification: **B**

In accordance with standards:

EN926-1:2015, EN926-2:2013+A1:2021

and NfL 2-565-20
Date of issue (DMY):

Manufacturer:

Model:

Serial number:

PG_2397.2024

21.03.2024

Niviuk Gliders / Air Games S.L.

Ikuma 3 P 20

IKUMA320FT

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight [kg]	75	Range of speed system [cm]	19.0
Minimum weight in flight [kg]	55	Speed range using brakes [km/h]	12
Glider's weight [kg]	2.9	Total speed range with accessories [km/h]	26
Number of risers	3+1	Range of trimmers [cm]	n/a
Projected area [m ²]	16.87		
Harness used for testing (max v	veight)	Inspections (whichever happens first)	
Harness type	ABS	every 100 hours of use or every 24 months	
Harness brand	Woody Valley srl		
Harness model	Wani Light 2 M	Person or company having presented the	
Harness to risers distance [cm]	43	glider for testing: None	
Distance between risers [cm]	43		

Route du Pré-au-Compte 8 * CH-1844 Villeneuve * +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes





Classification: **B**

In accordance with standards: EN926-1:2015, EN926-2:2013+A1:2021

and NfL 2-565-20

Date of issue (DMY):

Manufacturer:

Model: Serial number: PG_2303.2023

30.11.2023

Niviuk Gliders / Air Games S.L.

Ikuma 3 P 22

SI461928

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	85	Range of speed system (cm)	19.8
Minimum weight in flight (kg)	65	Speed range using brakes (km/h)	12
Glider's weight (kg)	3.2	Total speed range with accessories (km/h)	26
Number of risers	3+1	Range of trimmers (cm)	n/a
Projected area (m2)	18.58		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	every 100 hours of use or every 24 months	
Harness brand	Niviuk		
Harness model	Hamak M	Person or company having presented the	
Harness to risers distance (cm)	42	glider for testing: None	
Distance between risers (cm)	44		

9 10 11 12 13 14 15 19 20 21 22 23

Route du Pré-au-Compte 8 * CH-1844 Villeneuve * +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes





Classification: **B**

In accordance with standards: EN926-1:2015, EN926-2:2013+A1:2021

and NfL 2-565-20

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

PG_2304.2023

30.11.2023

Niviuk Gliders / Air Games S.L.

Ikuma 3 P 24

IKUMA3P24FT

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	95	Range of speed system (cm)	20.2
Minimum weight in flight (kg)	75	Speed range using brakes (km/h)	12
Glider's weight (kg)	3.4	Total speed range with accessories (km/h)	26
Number of risers	3+1	Range of trimmers (cm)	n/a
Projected area (m2)	20.28		
Harness used for testing (max weig	ıht)	Inspections (whichever happens first)	
Harness type	ABS	every 100 hours of use or every 24 months	
Harness brand	BGD GmbH		
Harness model	Snug M	Person or company having presented the	
Harness to risers distance (cm)	43	glider for testing: None	
Distance between risers (cm)	44		

9 10 11 12 13 14 15 18 19 20 21 22 23

Route du Pré-au-Compte 8 * CH-1844 Villeneuve * +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes





Classification: **B**

In accordance with standards: EN926-1:2015, EN926-2:2013+A1:2021

and NfL 2-565-20

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

PG_2305.2024

30.11.2023

Niviuk Gliders / Air Games S.L.

Ikuma 3 P 26

IKUMA3P26FT

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	105	Range of speed system (cm)	20.2
Minimum weight in flight (kg)	85	Speed range using brakes (km/h)	12
Glider's weight (kg)	3.7	Total speed range with accessories (km/h)	26
Number of risers	3+1	Range of trimmers (cm)	n/a
Projected area (m2)	21.99		
Harness used for testing (max	weight)	Inspections (whichever happens first)	
Harness type	ABS	every 100 hours of use or every 24 months	
Harness brand	Advance Thun AG		
Harness model	Success 4 M	Person or company having presented the	
		glider for testing: None	
Harness to risers distance (cm)	43	gider for testing. [40][e	
Distance between risers (cm)	48		

9 10 11 12 13 14 15 18 19 20 21 22 23

Route du Pré-au-Compte 8 * CH-1844 Villeneuve * +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes





Classification: **B**

In accordance with standards: EN926-1:2015, EN926-2:2013+A1:2021

and NfL 2-565-20

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

PG_2306.2023

30.11.2023

Niviuk Gliders / Air Games S.L.

Ikuma 3 P 28

SI461927

Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	115	Range of speed system (cm)	19.9
Minimum weight in flight (kg)	95	Speed range using brakes (km/h)	12
Glider's weight (kg)	4	Total speed range with accessories (km/h)	26
Number of risers	3+1	Range of trimmers (cm)	n/a
Projected area (m2)	23.69		
Harness used for testing (max	weight)	Inspections (whichever happens first)	
Harness type	ABS	every 100 hours of use or every 24 months	
Harness brand	Advance Thun AG		
Harness model	Success 4 M	Person or company having presented the	
Harness to risers distance (cm)	43	glider for testing: None	
Distance between risers (cm)	48		

18 19 20 21 22 23 15