

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2024/06/26

n. 1079242601/OE

Validity: 2029/06/25

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the	AIR GAMES SL Carrer del Ter 6-Nave D, La Cellera de Ter, Giron <mark>a</mark> – SPAIN		
PPE)			
Type of PPE:	Impact pad for paragliding harness		
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.		
Model	"DRIFO"		
Description:	, , , , ,	et pad to be fitted into paragliding harness. This impact pad is it can be detached from the harness.	
1	The complete material description and construction of this impact pad can be found in the Technical File of reference.		
	This impact pad is associat See pictures on page 2.	ted with the reference paragliding harness: DRIFTER 2 .	
Technical Standard:	EN 1651:2018+A1:2020	Paragliding equipment – Harnesses – Safety requirements and strength tests	
Intended use:	reduce the compression damage to the spine of the pilot in case of wrong landing in paragliding activities.		
Size range:	from S to L		
Technical File:	DC-17354		
Test report:	AIR-TURQUOISE SA n° PH_3	64.2022	



Certificato ue E rev06 - 01/02/22



PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

n. 1079242601/OE	Validity: 2029/06/25	
Prevent injuries caused by impacts that may occur in paragliding activities, by absorbing the impact energy to the body of the pilot.		
The protector passed the impact testing performed with a up to a minimum height of 165cm (measured from the impoint of the dummy). <u>Requirements:</u> • maximum peak value: 50 g; • at value of 38 g: maximum duration of 7 ms;		
at value of 20 g: maximum duration of 25 ms.		
 registered trademark and web site of the Manufacture item designation of the PPE; 	er;	
 size indication; date of manufacture; 		
 notice inviting the user to read the user manual; notice for removable impact pads as set out by the Store additional info: name/address of the test house and "N 		
	Prevent injuries caused by impacts that may occur in par the impact energy to the body of the pilot. The protector passed the impact testing performed with up to a minimum height of 165cm (measured from the im- point of the dummy). <u>Requirements:</u> • maximum peak value: 50 g; • at value of 38 g: maximum duration of 7 ms; • at value of 20 g: maximum duration of 25 ms. on a stitched label displaying the following information: • CE Marking ; • registered trademark and web site of the Manufacture • item designation of the PPE; • nr. and year of the European Standard of reference; • size indication; • date of manufacture; • test reference number; • notice inviting the user to read the user manual; • notice for removable impact pads as set out by the Sta	



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).



Certificato ue E rev06 - 01/02/22