



HOOK 5 P

User's manual



HOOK 5

PROGRESS AT EVERY LEVEL

WELCOME

We wish to welcome you to our team and thank you for your confidence in our glider product line.

We would like to share the enthusiasm with which we created this wing and the importance and care we took in the design and manufacture of this new model in order to offer maximum pleasure on every flight with a Niviuk glider.

Hook 5 P is not just a simple evolution of the previous model. Our designers started from scratch to better integrate the latest innovative technologies and produce the perfect glider to make the dream of flying and progressing come true.

A light version for weighty adventures. The Hook 5 P offers versatility, comfort and efficiency in a wing perfect for your first hike & fly tours. Your ultimate priority is ours too.

We are confident you will enjoy flying this glider and will soon discover the meaning of our name:

“The importance of small details”.

This is the user manual and we recommend you read it carefully.

The **NIVIUK Gliders** Team.

NIVIUK GLIDERS & AIR GAMES SL C/ DEL TER 6, NAVE D 17165 LA CELLERA DE TER - GIRONA - SPAIN

TEL. +34 972 42 28 78 FAX +34 972 42 00 86

info@niviuk.com www.niviuk.com

USER'S MANUAL

NIVIUK Gliders HOOK 5 P

This manual provides you with the necessary information on the main characteristics of your new paraglider.

Whilst it provides information on the wing, it cannot be viewed as an instructional handbook and does not offer the training required to fly this type of paraglider. Training can only be undertaken at a certified paragliding school and each country has its own system of licensing. Only the aeronautical authorities of respective countries can determine pilot competence.

The information in this manual is provided in order to warn you against adverse flying situations and potential dangers.

Equally, we would like to remind you that it is important to carefully read all the contents of your new HOOK 5 P manual.

Misuse of this equipment could lead to severe injuries or death. The manufacturers and dealers cannot be held responsible for misuse of the paraglider. It is the responsibility of the pilot to ensure the equipment is used correctly.

SUMMARY

WELCOME	2	4.4 FLYING WITHOUT BRAKE LINES	14
USER'S MANUAL	2	4.5 KNOT(S) IN FLIGHT	14
1. CHARACTERISTICS	4	5. LOSING ALTITUD	15
1.1 WHO IS IT DESIGNED FOR?	4	5.1 BIG EARS	15
1.2 CERTIFICATION	4	5.2 B-LINE STALL	15
1.3 IN-FLIGHT BEHAVIOUR	5	5.3 SPIRAL DIVE	15
1.4 CONSTRUCTION, MATERIALS	5	5.4 SLOW DESCENT THECNIQUE	16
1.5 ELEMENTS, COMPONENTS	8	6. SPECIAL METHODS	16
2. UNPACKING AND ASSEMBLY	8	6.1 TOWING	16
2.1 CHOOSE THE RIGHT LOCATION	8	6.2 ACROBATIC FLIGHT	16
2.2 PROCEDURE	8	7. FOLDING INSTRUCTIONS	17
2.3 CONNECTING THE HARNESS	8	7.1 MANTINANCE	17
2.4 TYPE OF HARNESS	8	7.2 STORAGE	17
2.5 SPEED BAR	8	7.3 CHECK AND INSPECTION	17
2.6 INSPECTION AND WING		7.4 REPAIRS	18
INFLATION ON THE GROUND	10	8. SAFETY AND RESPONSABILITY	18
2.7 ADJUSTING THE BRAKES	10	9. GUARANTEE	18
3. THE FIRST FLIGHT	10	10. ANNEXES	18
3.1 CHOOSE THE RIGHT PLACE	10	10.1 TECHNICAL DATA	19
3.2 PREPARATION	10	10.2 MATERIALS DESCRIPTION	20
3.3 FLIGHT PLAN	11	10.3 RISERS PLAN	21
3.4 PRE-FLIGHT CHECK LIST	11	10.4 SUSPENSION PLAN	22
3.5 WING INFLATION, CONTROL, AND TAKE-OFF	11	10.5 DIMENSIONS HOOK 5 P 20	23
3.6 LANDING	11	10.6 DIMENSIONS HOOK 5 P 22	23
3.7 PACKING	11	10.7 DIMENSIONS HOOK 5 P 24	24
4. IN FLIGHT	12	10.8 DIMENSIONS HOOK 5 P 26	24
4.1 FLYING IN TURBULENCE	12	10.9 DIMENSIONS HOOK 5 P 28	25
4.2 POSSIBLE CONFIGURATIONS	12	10.10 CERTIFICATION SPECIMEN TEST	26
4.3 ACCELERATED FLIGHT	14		



1. CHARACTERISTICS

1.1 WHO IS IT DESIGNED FOR?

Only the aeronautical authorities of respective countries can determine pilot competence.

The HOOK 5 P is the lightweight version of our progression wing, the Hook 5 P. With up to 1kg less weight, this new model is ideal for explorers who after making their debut in the world of paragliding decide to continue progressing with each flight, as well as for more experienced adventurers who prefer an intermediate, very safe wing.

With the new HOOK 5 P you too can discover and enjoy hike & fly or vol-biv adventures. A wing with an extremely reduced weight and volume so that from now on you can choose when, where and how to advance.

1.2 CERTIFICATION

Hook 5 P has been submitted for the European EN and LTF certification. All certification tests were performed at the Swiss testing house Air Turquoise. All sizes passed the load, shock and flight tests.

The load test proved that the wing can withstand the stipulated 8G.

The shock test proved that the wing can resist 1000 daN of force.

The flight test resulted in the following certification for all sizes:

EN A
LTF A

If the wing is loaded above the maximum certified take-off weight, the certification changes as follows:

EN B
LTF B

We recommend that only pilots who are familiar with gliders of this certification or above fly this Hook 5 P.

Only the aeronautical authorities of respective countries can determine pilot competence.

We recommend pilots read the flight test report carefully, especially the comments of the test pilot. The report contains all the necessary information on how the paraglider reacts during each of the tested manoeuvres.

It is important to note that different size wings will react differently during manoeuvres. Even within the same size, at maximum or minimum load, the behaviour and reactions of the wing may vary.

-Description of flight characteristics of LTF/EN A paragliders:
Paragliders with maximum passive safety and extremely forgiving flight characteristics. Gliders with good collapse resistance in normal flight.
-Description of the skills required by the pilot to fly an EN A wing:
Designed for all pilots, including pilots under instruction.

For further information on the flight test and the corresponding certification number, please see the final pages of this manual or see niviuk.com

1.3 IN-FLIGHT BEHAVIOR

Niviuk developed this wing by adopting very specific goals: to improve performance, excellent handling; to facilitate more control for the pilot.

To increase performance while maintaining the highest level of safety. To ensure that the wing transmits the maximum feedback in an understandable and comfortable way so that the pilot can focus on piloting and enjoying the flight. And, with smooth handling, take advantage of all favourable conditions.

In all aspects of flight, the wing is very solid and stable. The glide is smooth, even when fully accelerated. During glides, the wing maintains altitude and the wing remains stable. Improved turn precision means handling is less physical and provides better feedback. Inflating the wing is much easier and gentler, without overshooting.

Flying this wing is very intuitive, with clear and useful feedback about the airmass. It responds to the pilot's inputs effectively and even in thermic and turbulent conditions it remains stable and solid.

The HOOK 5 P flies efficiently. It enters thermals with sufficient speed to centre in the lift and climbs progressively. The handling is progressive and effective for even more flying pleasure under an exciting wing of extraordinary quality.

It is lightweight; even lighter in flight and easy to pilot, with outstanding turbulence buffering and a surprising range of speed for incredible glides.

1.4 CONSTRUCTION, MATERIALS

The paraglider has all the technological innovations used on other Niviuk gliders and is built with the most careful selection of current materials. It has all the current technology and accessories available to improve pilot comfort whilst increasing safety and performance.

In the design of all Niviuk products the team aims to ensure development and continuous improvement. The technologies developed in recent years have allowed us to develop greater, better wings. It is in this context that we would like to introduce the technologies included in this new model.

RAM Air Intake - this system is characterised by the arrangement of the air inlets, to ensure optimal maintenance of internal pressure. Thanks to this design, we were able to reduce their size, while maintaining the same air flow at all angles to improve laminar flow. More consistency across the whole speed range and better performance without compromising on safety.

Titanium Technology (TNT) – a revolutionary technique using titanium. Using Nitinol in the internal construction provides a more uniform profile and reduces the weight to gain efficiency in flight. Nitinol provides the highest level of protection against deformation, heat or breaks.

3D Pattern Cut Optimisation (3DP) – the latest generation of wings require a new fabric panel pattern and cutting system. Creating separate panels for each of the sections at the front of the wing means the sail fabric is more taut and crease-free. During the cutting, the optimal orientation of the fabric section is selected, depending on its final location. If the fabric pattern is properly aligned with the axes of load, it suffers less deformation after repeated use, to the long-term benefit of the leading edge.

3DL - adding an extra reinforced seam to the leading edge helps to ensure more consistency and volume in the profile. This provides a more efficient 3D contour.

Drag Reduction Structure (DRS) - the trailing edge has been reinforced with small ribs in order to distribute the pressure more evenly. This results in excellent manoeuvrability and greater control and precision.


Radial Sliced Diagonal (RSD) - a reinvention of the wing's internal structure. This new design is based on individual diagonal panels arranged in radial form, which increase the efficiency of the internal structure considerably.

Interlock System (IKS) - the IKS is an ultra-lightweight, high strength connecting system that aims to complement the light product range and replace the current systems based on the use of the maillons and/or carabiners. This new system is based on a secure connection using a simple Dyneema loop provided with a fixing and locking system, ensuring the complete efficiency and safety of the connection, and allowing the equipment to be ready at all times with any load.

IKS1000 is designed and dimensioned as a connection system between the risers and the lines. It has a breaking load of 1055 kg, which greatly exceeds that of the classic 3mm (550 kg) maillon, but with much less weight. This feature makes it a key element in the entire range of P-Series (lightweight) wings, which are delivered with this technology as standard.

Please note: the IKS1000 kg system was not designed nor certified to connect the risers to the harness and/or a rescue parachute to the harness. For that specific function, Niviuk developed the IKS3000. For more information visit niviuk.com

IKS INSTRUCTIONS



1. Locate the elastic sleeve's inner small diameter tube.
2. Push the IKS line through it. Only push it through the inner channel once.
3. Now push the IKS line through the line loops and the riser. The reinforced end with the black tab should be located on the side of the riser.
4. Push the upper looped end downward through the elastic sleeve (not the small diameter tube) and then through the reinforced loop end where the black tab is located.
5. Pass this same end through the riser.
6. Now pass the end back through the sleeve (not through the channel) and then through the line loops.
7. Re-pass it through the sleeve (not through the channel) and then through the reinforced end loop.

8. Thread the reinforced end tab through the loop at the other end.
9. Pull the tab tight to secure the knot and connection.

The use of these technologies is a big technological leap forward in building wings and a big improvement in flight comfort.

For the HOOK 5 P lines, Liros Dyneema is combined with Edelrid aramid in the mid/gallery lines and the main lines are made from sheathed TNL.

Both the Dyneema and the aramid lines are unsheathed, which makes them exposed to the abrasions common in our sport. This means that the lines must be professionally checked periodically every 100 flight hours. This means that we must be aware that the glider is made from high-performance materials that need a thorough pre-flight check before each flight.

For the construction process of the Hook 5 P we use the same criteria, quality controls and manufacturing processes as in the rest of our range. From Olivier Nef's computer to fabric cutting, the operation does not allow for even a millimetre of error. The cutting of each wing component is performed by a rigorous, extremely meticulous, automated computer laser-cutting robotic arm.

This program also paints the guideline markers and numbers on each individual fabric piece, thus avoiding errors during this delicate process. The jigsaw puzzle assembly is made easier using this method and optimises the operation while making the quality control more efficient. All Niviuk gliders go through an extremely thorough and detailed final inspection. The canopy is cut and assembled under strict quality control conditions facilitated by the automation of this process.

Every wing is individually checked with a final visual inspection. The fabric used to manufacture the glider is light, resistant and durable. The fabric will not experience fading and is covered by our warranty.

The line diameter has been calculated depending on the workload and aims to achieve the required best performance with the least drag. The sheath protects the line cores from UV rays and abrasions.

The lines are semi-automatically cut to length and all the sewing is completed under the supervision of our specialists.

Every line is checked and measured once the final assembly is concluded.

Each glider is packed following specific maintenance instructions as recommended by the fabric manufacturer.

Niviuk gliders are made of premium materials that meet the requirements of performance, durability and certification that the current market demands.

Information about the various materials used to manufacture the wing can be viewed in the final pages of this manual.

1.5 ELEMENTS, COMPONENTS

The HOOK 5 P is delivered with a series of accessories that will greatly assist you in the maintenance of your paraglider:

- A Kargo bag. This bag is large enough to hold all equipment comfortably and with plenty of space.
- An inner bag to protect the wing during storage and transport.
- An adjustable compression strap to compress the inner bag and reduce its volume.
- A protective riser bag to avoid damage.
- A repair kit with self-adhesive Ripstop tape in the same colour as the wing and spare O-rings to protect the maillons.

2. UNPACKING AND ASSEMBLY

2.1 CHOOSING THE RIGHT LOCATION.

We recommend unpacking and assembling the wing on a training hill or a flat clear area without too much wind and free of obstacles. It will help you to carry out all the recommended steps required to check and inflate the HOOK 5 P.

We recommend the whole installation procedure is supervised by a qualified professional instructor or official dealer. Only they can address any doubts in a safe and professional way.

2.2 PROCEDURE

Take the paraglider out of the rucksack, open and unfold it on the ground with the lines positioned on the undersurface, oriented in the direction of inflation. Check the condition of the fabric and the lines for defects. Check the IKS connecting the lines to the risers to make sure they are fully closed and tightened. Identify, and if necessary untangle, the A, B and C-lines, the brake lines and corresponding A+A'/B/C risers. Make sure that there are no knots.

2.3 CONNECTING THE HARNESS

The Hook 5 P risers are colour-coded.

- Right: green
- Left: red

This colour-coding makes it easier to connect the wing to the correct side and helps prevent pre-flight errors.

Correctly connect the risers to the attachment points so that the risers and lines are correctly ordered and free of twists. Check that the IKS and carabiners are properly fastened and securely locked.

2.4 TYPE OF HARNESS

The Hook 5 P can be flown with all current harness types, including those with a pod. We recommend setting the chest strap to the distance specified in the certification report - this will vary depending on size.

We recommend adjusting the chest strap to the certification distance, which is between 42 and 50 cm between the carabiners of the harness. This adjustment will offer the best compromise between safety and feeling the wing.

Any change in these adjustments may affect the performance and reactions of the wing rendering its certification invalid.

2.5 SPEED-BAR

The speed-bar is a means of temporary acceleration by changing the flow over the profile. The speed system comes pre-installed on the risers and is not modifiable as it conforms to the measurements and limits stipulated in its certification.

The Hook 5 P includes a speed system with a maximum travel of 13 cm. The speed system is engaged when the pilot pushes the speed-bar - not included as standard with this glider model - with their feet (see 2.5.1 Speed system assembly)

The speed system uses an action/reaction system. Released, the speed-bar is set to neutral. When the bar is pushed using the feet, the wing accelerates. The speed can be regulated by varying the pressure on the bar. Once the pressure on the bar is released, the speed system returns to the neutral setting.

The speed system is efficient, sensitive and precise. The pilot can use the system whenever they want during the flight. In the neutral position the glider will fly at the standard speed and glide. Using full speed-bar, the wing will fly at maximum speed, but the glide will be adversely affected.

- Released speed-bar: the A, B, C and D-risers are aligned.
- Full speed-bar: the difference between the A - C-risers becomes:13 cm.


Please note!

The use of the speed system results in changes to the speed and reactions of the wing. For more information, please see the certification report.

2.5.1 SPEED SYSTEM ASSEMBLY.


The speed-bar consists of the bar that the pilot pushes with their feet, as well as the two cords that connect it to the speed system components on the risers. Once you have chosen the type of speed-bar you prefer, you must install it. Some considerations:

- You should use the type of speed-bar you consider appropriate, depending on the type of harness, personal preferences, etc.
- The speed-bar is detachable to facilitate its connection and / or disconnection to the risers as well as subsequent adjustment.
- To connect it to the harness, please follow the instructions of the harness manufacturer. The majority of harnesses have a speed system pre-installed.
- The standard connection of the speed-bar to the speed system is via Brummel hooks, where two slots in the hooks are interlocked, making their connection / disconnection easy. However, any connection system that is safe may be used.



Plume (P) models - please note

The P models were designed with the idea of saving weight across the entire equipment. To achieve this, Niviuk decided to deliver the wings without the classic Brummel hooks and opting for a kite-style knotting system. This system offers the same efficiency and safety as the classic Brummel hooks, but with much less weight.



- 1.Make a knot in the speed-bar cord and we pass this through the cord connections on the risers.
- 2.Apply tension to both sides until the knots are locked tightly in the riser connections.

The system or procedure for connecting the kite knot is exactly the same as the Brummel hooks and can be used in other systems or connection elements.

2.5.2 CHANGING THE RISER CORDS.

In spite of the speed system having pulleys with bearings to reduce friction to a minimum, the frequency with which the speed-bar is used causes the cord to wear and you may need to replace them. In all Niviuk gliders the speed system cords on the risers are completely removable and easily replaceable. You can use the Brummel hooks, not use them, remove them, use another type of connector, etc. It is even possible to fix the speed-bar cords directly to the speed system on the risers. This last option makes the connection / disconnection more laborious, but means the cord has maximum travel without obstructions or restrictions which is very useful for some models of harnesses.

2.6 INSPECTION AND WING INFLATION ON THE GROUND

After your gear has been thoroughly checked and the weather conditions deemed favourable for flying, inflate your HOOK 5 P as many times as necessary to familiarise yourself with its behaviour.

Inflating the HOOK 5 P is easy and should not require a great deal of physical effort. Inflate the wing with a little pressure from the body using the harness. This may be assisted by using the A-lines. Do not pull on them; just accompany the natural rising movement of the wing. Once the wing is inflated to the overhead position, appropriate control with the brakes will be sufficient to hold it there.

2.7 ADJUSTING THE BRAKES

The length of the main brake lines are adjusted at the factory and conform to the length stipulated during certification. However, they can be changed to suit your flying style. It is advisable to fly with the original setting for a period of time to get used to the actual behaviour of the HOOK 5. In case it is necessary to modify the brake length, loosen the knot, slide the line through the brake handle to the desired point and re-tighten the knot firmly. Only qualified personnel should carry out this adjustment. You must ensure that the modification does not affect the

trailing edge and slow the glider down without pilot input. Both brake lines should be symmetrical and the same length. We recommend using a clove hitch or bowline knot.

When changing the brake length, it is necessary to check that they do not engage when the speed-bar is used. When we accelerate, the glider rotates over the C-riser and the trailing edge elevates. It is important to check that the brake is adjusted to take into consideration this extra distance during acceleration. With this profile deformation there is a risk of generating turbulence and causing a frontal or asymmetric collapse.

3. THE FIRST FLIGHT

3.1 CHOOSE THE RIGHT PLACE

For the first flight we recommend going to your usual flying area and that a qualified instructor is present and supervising the entire procedure.

3.2 PREPARATION

Repeat the procedures detailed in chapter 2 UNPACKING AND ASSEMBLY in order to prepare your equipment.

3.3 FLIGHT PLAN

Planning a flight before taking off to avoid possible problems later is always a good idea.

3.4 PRE-FLIGHT CHECK LIST

Once ready, but before taking off, conduct another equipment inspection. Conduct a thorough visual check of your gear with the wing fully open, the lines untangled and properly laid out on the ground to ensure that all is in working order. Be certain the weather conditions are suited to your flying skill level.

3.5 WING INFLATION, CONTROL, AND TAKE-OFF

The HOOK 5 P comes up easily, without requiring additional energy, and does not overfly you. It is a straight-forward exercise, leaving enough time for you to decide whether to accelerate and take off or not.

If the wind permits, we recommend a reverse launch, as this allows a better visual inspection of the wing during inflation. In “strong” winds, the hook 5 is especially easy to control using this launch technique. Winds of 25 to 30 km/h are considered strong for paragliding.

Correctly setting up the wing on the ground before takeoff is especially important. Choose an appropriate location facing the wind. Position the paraglider in a crescent configuration to facilitate inflation. A clean wing layout will ensure a trouble-free take off.

3.6 LANDING

The HOOK 5 P lands excellently, it converts the wing speed into lift at your demand, allowing an enormous margin of error. Wrapping the brake lines around your hand to get greater braking efficiency is not necessary.

3.7 PACKING

The Hook 5 P has a complex leading edge, manufactured using a variety of different materials and it must be packed carefully. A correct folding method is very important to extend the useful life of your paraglider.

It should be concertina-packed, with the leading edge reinforcements flat and the flexible rods stacked one on top of the other. This method will keep the profile in its original shape and protect the integrity of the wing over time. Make sure the reinforcements are not bent or folded. It should not be folded too tightly to avoid damage to the cloth and/or lines.

At Niviuk we have designed the NKare Bag, a bag designed to assist you with rapid packing which helps maintain the integrity of the leading edge and its internal structures in perfect condition.

The NKare Bag guides you through the folding process, allowing you to concertina pack the wing with each rod on top of the other and then fold the wing as required. This folding system ensures that both the fabric and the reinforcements of the internal structure are kept in perfect condition.

4. IN FLIGHT

We recommend that you read the certification test report.

The report contains all the necessary information on the HOOK 5 reacts during each of the tested manoeuvres.

It is important to point out that the appropriate response to each adverse manoeuvre can vary from size to size; even within the same size at maximum or minimum load the behaviour and reactions of the wing may vary.

Having the knowledge that the testing house provides through the test report is fundamental to learning how to deal with possible situations.

To become familiar with the manoeuvres described below, we recommend practising within the auspices of a licensed training outfit.

4.1 FLYING IN TURBULENCE

The HOOK 5 P has an excellent profile to deal with incidents; it is very stable in all conditions and has a high degree of passive safety, even in turbulent conditions.

All paragliders must be piloted for the prevailing conditions and the pilot is the ultimate safety factor.

We recommend active flying in turbulent conditions, always taking measures to maintain control of the wing, preventing it from collapsing and restoring the speed required by the wing after each correction.

Do not correct the glider (braking) for too long in case this provokes a stall. If you have to take corrective action, make the input then re-establish the correct flying speed.

4.2 POSSIBLE CONFIGURATIONS

To become familiar with the manoeuvres described below, we recommend practising within the environment of a licensed training outfit. You must adapt your use of the brakes depending on the wing-loading and avoid over-steering.

It is important to note that the type of reaction to a manoeuvre can vary from one size of wing to another, and even within the same size the behaviour and reactions may be different depending on the wing-loading.

In the test report, you will find all the necessary information on how to handle your new wing during each of the tested manoeuvres. Having this information is crucial to know how to react during these manoeuvres in real flight, so you can deal with these situations as safely as possible.

Asymmetric collapse

In spite of the HOOK 5' P 's profile stability, strong turbulent air may cause the wing to collapse asymmetrically in very strong turbulence, especially if you do not fly actively and prevent the collapse. In this case the glider conveys a loss of pressure through the brake lines and the harness.

To prevent the collapse from happening, pull the brake handle on the affected side of the wing. It will increase the incidence of the wing (angle of attack). If the collapse does happen, the HOOK 5 will not react violently, the turning tendency is gradual and easily controlled. Weight-shift toward the open, flying side (the opposite side of the collapse) to keep the wing flying straight, while applying light brake pressure to that side if necessary. Normally, the collapsed side of the wing should then recover and reopen by itself. If it does not, try to weight-shift towards the collapsed side. If this does not resolve the issue, pull the brake handle on the collapsed

side decisively and quickly all the way (100%) down and release it back up immediately. You may have to repeat this action to provoke the re-opening of the collapsed glider side. Do not over-brake or slow down the flying side of the wing (control the turn). Once the collapsed side is open make sure you return to normal flying speed.

Frontal collapse

Due to the HOOK 5 P 's design, in normal flying conditions frontal collapses are unlikely to take place. The wing's profile has great buffering abilities when dealing with extreme incidence changes. A frontal collapse may occur in strong turbulent conditions, entering or exiting powerful thermals. Frontal collapses usually re-inflate without the glider turning, but a symmetrically applied quick braking action with a quick deep pump of both brakes will accelerate the re-inflation if necessary. Release the brake lines immediately to return to default glider air speed.

Negative spin

A negative spin does not conform to the HOOK 5's normal flight behaviour. Certain circumstances however, may provoke a negative spin (such as trying to turn when flying at very low air speed whilst applying a lot of brake). It is not easy to give any specific recommendation about this situation other than quickly restoring the wing's default air speed and angle of attack by progressively reducing the tension on the brake lines. The normal wing reaction will be to have a lateral surge on the re-accelerated side with a rotation not greater than 360° before returning to default air speed and a straight flight path trajectory.

Parachutal stall

The possibility of entering or remaining in a parachutal stall have been eliminated from the HOOK 5 P.

A parachutal stall is virtually impossible with this wing. If it did enter into a parachutal stall, the wing loses forward motion, becomes unstable and there is a lack of pressure on the brake lines, although the canopy appears to be fully inflated. To regain normal air speed, release brake line tension symmetrically and manually push on the A-lines or weight-shift your body to any side WITHOUT PULLING ON THE BRAKE LINES.

Deep Stall

The possibility of the HOOK 5 stalling during normal flight is very unlikely. It could only happen if you are flying at a very low air speed, whilst oversteering or performing dangerous manoeuvres in turbulent air.

To provoke a deep stall, the wing has to be slowed down to its minimum air speed by symmetrically pulling the brake lines all the way (100%) down until the stall point is reached and held there. The glider will first pitch rearward and then reposition itself overhead, rocking slightly, depending on how the manoeuvre is done.

When entering a stall, remain clear-headed and ease off the brake lines until reaching the half-way point of the total brake travel. The wing will then surge violently forward and could reach a point below you. It is most important to maintain brake pressure until the glider has returned to its default overhead flying position.

To resume normal flight conditions, progressively and symmetrically release the brake line tension to regain air speed. When the wing reaches the overhead position, the brakes must be fully released. The wing will then surge forward to regain full air speed. Do not brake excessively at this moment as the wing needs to accelerate to pull away from the stall configuration. If you have to control a possible frontal collapse, briefly pull both brake handles down to bring the wing back up and release them immediately while the glider is still in transition to reposition itself overhead.

Cravat

A cravat may happen after an asymmetric collapse, when the end of the wing is trapped between the lines. Depending on the nature of the tangle, this situation could rapidly cause the wing to spin. The corrective manoeuvres to use are the same as those applied in case of an asymmetric collapse: control the turn/spin by applying tension on the opposite brake and weight shift opposite to the turn. Then locate the 3STI stabilo line (attached to the wing tip) trapped between the other lines. This

line has a different colour and is located on the outside position of the B-riser.

Pull this line until it is taut. This action will help to release the cravat. If ineffective, fly down to the nearest possible landing spot, controlling the direction with both weight-shift and the use of the brake opposite to the tangled side. Be cautious when attempting to undo a tangle while flying near terrain or other paragliders; it may not be possible to continue on the intended flight path.

Over-controlling

Most flying problems are caused by wrong pilot input, which then escalates into a cascade of unwanted and unpredicted incidents. We should note that the wrong inputs can lead to loss of control of the glider. The HOOK 5 was designed to recover by itself in most cases. Do not try to over-correct it!

Generally speaking, the reactions of the wing, which are caused by too much input, are due to the length of time the pilot continues to over-control the wing. You have to allow the glider to re-establish normal flying speed and attitude after any type of incident.

4.3 ACCELERATED FLIGHT

The HOOK 5 P 's profile was designed for stable flight throughout its entire speed range. The speed-bar can be used in strong winds or significant sink.

When accelerating the wing, the profile becomes more sensitive to turbulence and closer to a possible frontal collapse. If a loss in internal wing pressure is felt, tension on the speed-bar should be reduced to a minimum and a slight pull on the brake lines is recommended to increase the wing's incidence angle. Remember to re-establish the air speed after correcting the angle of attack.

It is NOT recommended to accelerate near obstacles or in very turbulent

conditions. If necessary, constantly adjust the movements and pressure on the speed-bar whilst doing the same to the brake lines. This balance is considered to be 'active piloting'.

4.4 FLYING WITHOUT BRAKE LINES

If, for any reason at all, the HOOK 5 P 's brake lines become disabled in flight, it will become necessary to pilot the wing with the C-risers and weight shifting until landing. These risers steer easily because are not under significant tension. You will have to be careful and not handle them too heavily in case this causes a stall or negative spin. The wing must be flown at full speed (not accelerated) during the landing approach, and the C-risers will have to be pulled symmetrically all the way down shortly before contact with the ground. This braking method is not as effective as using the brake lines, and hence the wing will land with a higher ground speed.

4.5 LINE KNOT(S) IN FLIG

The best way to avoid knots and tangles is to thoroughly inspect the lines as part of a systematic pre-flight check. If a knot is spotted during the take off phase, immediately abort the launch sequence and stop.

If inadvertently taking off with a knotted line, the glider drift will need to be compensated by weight-shifting to the opposite side and applying a slight brake pull to that side. Gently pull the brake line to see if the knot can be undone or try to locate the problem line. Try pulling it to see if the knot can be undone. Beware of trying to clear a knotted line or untangle a line in flight when close to the terrain. If the knot is too tight and cannot be undone, carefully and safely fly to the nearest landing zone. Be careful: do not pull too hard on the brake handles because there will be an increased risk of stalling the wing or entering a negative spin. Before attempting to clear a knot, make sure there are no other pilots flying in the vicinity.

5. LOSING ALTITUDE

Knowledge of different descent techniques could become vital in certain situations. The most suitable descent method will depend on the particular situation.

To become familiar with the manoeuvres described below, we recommend practising within the environment of a licensed training outfit.

5.1 BIG EARS

Big ears is a moderate descent technique, able to increase the sink rate to -3 or -4 m/s and reduces the ground speed by 3 to 5 km/h. The angle of attack and effective wing-loading will also increase due to the smaller surface area of the wing.

Standard technique

To perform the 'Big ears' manoeuvre, take the outermost line on each 3A3 riser and simultaneously, smoothly pull them outward and downward. The wingtips will fold in. To re-establish forward speed and the correct angle of attack, accelerate once the ears are pulled. Keep the ears pulled in until you have lost the desired altitude. Let go of the lines to re-inflate the tips automatically. If they do not, try progressively pulling one brake then the other. We recommend inflating the wing tips asymmetrically, without major change to the angle of attack, especially when flying near the ground or flying in turbulence.

Beware of the risk of stalling!

The action of reaching for the outermost A-lines (3A3 lines) to pull the ears, can inadvertently mean pulling the brakes. The same can happen when we are holding the tips down with the outermost A-lines (3A3 lines), it is possible to accidentally affect the brakes. This can obviously lead to a significant speed decrease.

In paragliders with a very pronounced arc, pulling big ears means an increase in drag. On a very arched wing, the ears do not fold, they just hang. The increase of drag is more pronounced than on wings with a less pronounced arc.

The HOOK 5 P is designed with little chord, which is good in normal flight conditions. However, this same damping is what can cause us to have problems to regain normal flying speed after a high increase of the angle of attack and the added drag of the ears.

These particularities, together with turbulent thermic conditions, could cause an unintentional stall.

The solution: big ears may still be applied but you must be fully aware of the above-mentioned points and act accordingly. To avoid the stall, simply use half speed-bar (this is sufficient) to increase the speed and decrease the angle of incidence. This should allow you to maintain sufficient speed to prevent the stall. Take care not to pull the brakes while making the ears as this will make a stall more likely!

5.2 B-LINE STALL

When carrying out this manoeuvre, the wing stops flying, loses all horizontal speed and the pilot is no longer in control of the paraglider.

The airflow over the profile is interrupted and the wing enters a situation similar to parachuting.

To enter this manoeuvre, the B-risers are gripped below the maillons and symmetrically pulled down together (approx. 20-30 cm) and maintained in that position.

Initiating the maneuver is physically demanding because it can take some strength to pull the risers down until the wing is deformed. After this, the physical effort is less. Continue to hold the risers in position. Once the wing is deformed, its horizontal speed will drop to 0 km/h; vertical descending speed increases to -6 to -8 m/s, depending on the conditions and how the manoeuvre is performed.

To exit the manoeuvre, simultaneously release both risers. The wing will then slightly surge forward and automatically return to normal flight. It is better to let go of the lines quickly rather than slowly.

This is an easy descent technique to perform, but remember that the wing will stop flying, will lose all forward horizontal speed, and its reactions will change markedly when compared to a normal flight configuration.

5.3 SPIRAL DIVE

This is a more effective way to rapidly lose altitude. Beware that the wing will experience and be subjected to a tremendous amount of descending and rotating speed (g-force), which can cause a loss of orientation and consciousness (blackout). This manoeuvre must therefore be done gradually to increase one's capacity to resist the g-force exerted on the body. With practise, you will fully appreciate and understand it. Only practise this manoeuvre at high altitude and with enough ground clearance.

To start the manoeuvre, first weight shift and pull the brake handle located on the inner side of the turn. The intensity of the turn can be controlled by braking slightly using the outer brake handle.

A paraglider flying at its maximum rotating speed can reach -20 m/s, or the equivalent of a 70 km/h vertical descent, and will stabilise in a spiral dive from 15m/s onwards.

Good enough reasons to familiarise yourself with the manoeuvre and understand how to exit it.

To exit this manoeuvre, the inner brake handle (down side of the turn) must progressively be relaxed while momentarily applying tension to the outer brake handle opposite to the turn. The pilot must also weight shift and lean towards the opposite side of the turn at the same time.

The exit should be performed gradually and smoothly so that the changes in pressure and speed can be noted.

When exiting the spiral, the glider will briefly experience an asymmetrical acceleration and dive, depending on how the manoeuvre was carried out.

Practise these manoeuvres at sufficient altitude and carefully.

5.4 SLOW DESCENT TECHNIQUE

This technique allows descent without straining the wing or taxing the pilot. Glide normally while searching for descending air and begin to turn as if climbing in a thermal, but with the intention to sink.

Common sense has to be used to avoid dangerous areas of rotor when looking for descending air. Safety first!

6. SPECIAL METHODS

6.1 TOWING

The HOOK 5 P does not experience any problem whilst being towed. Only qualified winch personnel should handle the certified equipment to carry out this operation. The wing must be inflated similarly as during a normal take off.

It is important to use the brakes to correct the flight path alignment, especially if the glider begins to turn. Since the wing is subject to a slow airspeed and with a high positive angle of attack, we must make any corrections with a high degree of feel and delicacy, in order to avoid a stall.

6.2 ACROBATIC FLIGHT

Although the HOOK 5 P was tested by expert acrobatic pilots in extreme situations, it was not designed for it. We do not recommend using this glider for acrobatic flying!!!

We consider acrobatic flights to be any form of piloting different than standard flights. Learning acrobatic manoeuvres should be conducted under the supervision of qualified instructors within a school environment and over water with all safety/rescue elements in place. Centrifugal forces as high as 4 to 5 g can be exerted on the body and wing during extreme manoeuvres.

7. FOLDING INSTRUCTIONS

7.1 MAINTENANCE

Niviuk we are firmly committed to make technology accessible to all pilots. Therefore our wings are equipped with the latest technological advances gained from the experience of our R&D team.

Careful maintenance of your equipment will ensure continued top performance. Apart from the general checks, we recommend actively maintaining your equipment.

A pre-flight check is obligatory before each flight. If there is any damage to the equipment or you suspect any areas of the wing are susceptible to wear, you should inspect these and act accordingly.

All incidents involving the leading edge should be reviewed. A hard impact of the leading edge against a hard surface can damage the sail cloth.

Unsheathed lines provide increased performance, but this means more care should be taken when using and maintaining the wing.

Thanks to TNT, the wing has more safety and performance, but this means being more careful with the material. If any Nitinol rod is damaged, they are easily replaceable.

The fabric and the lines do not need to be washed. If they become

dirty, clean them with a soft damp cloth, using only water. Do not use detergents or other chemicals.

If your wing is wet from contact with water, place it in a dry area, air it and keep it away from direct sunlight.

Direct sunlight may damage the wing's materials and cause premature aging. After landing, do not leave the wing exposed to the sun. Pack it properly and stow it away in its backpack.

If your wing is wet from contact with salt water, immerse it in fresh water and dry it away from direct sunlight.

7.2 STORAGE

It is important for the wing to be correctly folded when stored. Keep it in the in a cool, dry place away from solvents, fuels, oils.

Do not leave your gear inside a car boot, as cars left in the sun can become very hot. A rucksack can reach temperatures up to 60°C.

Weight should not be laid on top of the equipment.

It is very important to pack the wing correctly before storage.

In case of long-term storage it is advisable, if possible, that the wing is not compressed and it should be stored loosely without direct contact with the ground. Humidity and heating can have an adverse effect on the equipment.

7.3 CHECKS AND INSPECTIONS

The HOOK 5 P must be periodically serviced. An inspection must be scheduled every 100 flying hours or every two years whichever comes first (EN/LTF norm).

We strongly recommend that any repairs should be done in a specialist repair shop by qualified personnel.

This will guarantee the airworthiness and continued certification of your HOOK 5 P.

A thorough pre-flight check must be performed before every flight.

7.4 REPAIRS

In the case of small tears, you can temporarily repair these by using the Ripstop tape included in the repair kit, as long as no stitching is required to mend the fabric.

Any other tears or repairs should be done in a specialist repair shop by qualified personnel.

Damaged lines must be repaired or exchanged immediately.

Please refer to the line plan at the end of this manual.

Any repair should be done in a specialist repair shop by qualified personnel.

Niviuk cannot be held responsible for any damage caused by incorrect repairs.

8. SAFETY AND RESPONSIBILITY

It is well known that free-flying with a paramotor or trike is considered a high-risk sport, where safety depends on the person who is practicing it.

Incorrect use of this equipment may cause severe, life-changing injuries to the pilot, or even death.

Manufacturers and dealers cannot be held responsible for your decisions, actions or accidents that may result from participating in this sport.

You must not use this equipment if you have not been properly trained to use it. Do not take advice or accept any informal training from anyone who is not properly qualified as a flight instructor

9. GARANTEE

The equipment and components are covered by a 2-year warranty against any manufacturing defect.

The warranty does not cover misuse of the equipment.

DISCLAIMER: Paragliding is an activity that requires concentration, specific knowledge and common sense. Take care! You should learn to paraglide under the auspices of a certified flying school. Take out personal insurance and make sure you have all the correct licences. Be modest when you evaluate your skill level in terms of meteorology.

Niviuk's liability for damages covers only its own products.

Niviuk can take no responsibility for your actions. When flying, accept the risk involved.

10. ANNEXES

10. TECHNICAL DATA

10.1 TECHNICAL DATA

			20	22	24	26	28
CELLS	NUMBER		47	47	47	47	47
ASPECT RATIO	FLAT		5,3	5,3	5,3	5,3	5,3
AREA	FLAT	m2	20	22	24	26	28
	PROJECTED	m2	17,06	18,76	20,47	22,17	23,88
CORD	MAXIMUM	m	2,42	2,54	2,66	2,76	2,87
LINES	TOTAL	m	207	218	228	238	247
	MAIN		2/1/3/2	2/1/3/2	2/1/3/2	2/1/3/2	2/1/3/2
RISERS	NUMBER	3+1	A/A'/B/C	A/A'/B/C	A/A'/B/C	A/A'/B/C	A/A'/B/C
	ACCELERATOR	mm	130	130	130	130	130
GLIDER WEIGHT		kg	3,15*	3,4	3,7	3,9*	4,15*
TOTAL WEIGHT IN FLIGHT (TWF)	MIN - MAX	kg	55-70	60-80	70-92	82-105	95-120
CERTIFICATION TWF	EN/LTF		A+	A+	A+	A+	A+
TWF EXTENDED	MIN - MAX	kg	55-85	60-95	70-105	82-120	-
CERTIFICATION TWF EXTENDED	EN/LTF		B	B	B	B	B

10.2 MATERIALS DESCRIPTION

CANOPY	FABRIC CODE	SUPPLIER
UPPER SURFACE	70032 E3W	PORCHER IND (FRANCE)
BOTTOM SURFACE	70000 E3H	PORCHER IND (FRANCE)
PROFILES	70000 E91 / 70032 E4D	PORCHER IND (FRANCE)
DIAGONALS	70000 E91 / 70032 E4D	PORCHER IND (FRANCE)
LOOPS	LKI - 10	KOLON IND. (KOREA)
REINFORCEMENT LOOPS	W-420	D-P (GERMANY)
TRAILING EDGE REINFORCEMENT	MYLAR	D-P (GERMANY)
RIBS REINFORCEMENT	LTN-0.8 STICK	SPORTWARE CO.CHINA
THREAD	SERAFIL 60	AMAN (GERMANY)


SUSPENSION LINES	FABRIC CODE	SUPPLIER
UPPER CASCADES	DC - 60	LIROS GMHB (GERMANY)
UPPER CASCADES	A-8000/U 50	EDELRID (GERMANY)
UPPER CASCADES	A-8000/U 70	EDELRID (GERMANY)
UPPER CASCADES	A-8000/U 130	EDELRID (GERMANY)
MIDDLE CASCADES	A-8000/U 50	EDELRID (GERMANY)
MIDDLE CASCADES	A-8000/U 90	EDELRID (GERMANY)
MIDDLE CASCADES	A-8000/U 130	EDELRID (GERMANY)
MIDDLE CASCADES	A-8000/U 230	EDELRID (GERMANY)
MIDDLE CASCADES	TNL - 80	TEIJIM LIMITED (JAPAN)
MAIN	TNL - 80	TEIJIM LIMITED (JAPAN)
MAIN	TNL - 280	TEIJIM LIMITED (JAPAN)

MAIN	TNL - 280	TEIJIM LIMITED (JAPAN)
MAIN BREAK	TNL - 280	TEIJIM LIMITED (JAPAN)
THREAD	SERAFIL 60	AMAN (GERMANY)


RISERS	FABRIC CODE	SUPPLIER
MATERIAL	3455	COUSIN (FRANCE)
COLOR INDICATOR	PAD	TECNI SANGLES (FRANCE)
THREAD	V138	COATS (ENGLAND)
CONNECTIONS	IKS-1000	COUSIN (FRANCE)
PULLEYS	RF25109	RONSTAN (AUSTRALIA)

10.3 RISERS PLAN

A	A'	B	C
3A1	3A3	4B1	4C1
3A2		4B2	4C2
		stb	



10.4 SUSPENSION PLAN



10.5 DIMENSIONS HOOK 5 P 20

LINES HEIGHT mm

	A	B	C	D	br
1	5861	5762	5802	5910	6423
2	5804	5701	5752	5858	6234
3	5734	5694	5768	5868	6155
4	5660	5574	5623	5717	6092
5	5598	5517	5577		5936
6	5472	5430	5498		5872
7	5392	5396	5479		5908
8	5333	5388	5491		5865
9	5112	5088	5086		5741
10	5018	5020			5641
11					5623
12					

RISERS LENGHT mm

	A	B	C	
	470	470	470	STANDARD
	340	380	470	ACCELERATED

10.6 DIMENSIONS HOOK 5 P 22

LINES HEIGHT mm

	A	B	C	D	br
1	6161	6064	6109	6222	6770
2	6106	6004	6054	6166	6569
3	6037	6008	6089	6196	6487
4	5960	5886	5945	6043	6434
5	5901	5822	5880		6270
6	5769	5731	5798		6200
7	5677	5698	5782		6241
8	5620	5694	5800		6196
9	5414	5390	5393		6067
10	5318	5320			5963
11					5949
12					

RISERS LENGHT mm

	A	B	C	
	470	470	470	STANDARD
	340	380	470	ACCELERATED

10.7 DIMENSIONS HOOK 5 P 24

LINES HEIGHT mm

	A	B	C	D	br
1	6454	6344	6408	6522	7093
2	6398	6286	6350	6466	6885
3	6334	6297	6385	6495	6799
4	6255	6171	6239	6337	6741
5	6200	6109	6167		6571
6	6063	6014	6089		6504
7	5972	5976	6069		6546
8	5908	5969	6084		6500
9	5696	5667	5663		6364
10	5585	5585			6254
11					6247
12					

RISERS LENGHT mm

	A	B	C	
	470	470	470	STANDARD
	340	380	470	ACCELERATED

10.8 DIMENSIONS HOOK 5 P 26

LINES HEIGHT mm

	A	B	C	D	br
1	6742	6626	6689	6811	7396
2	6686	6569	6639	6760	7181
3	6616	6578	6668	6781	7095
4	6540	6449	6509	6618	7034
5	6473	6379	6445		6857
6	6331	6282	6359		6785
7	6237	6247	6338		6831
8	6174	6246	6359		6783
9	5944	5924	5920		6646
10	5844	5845			6532
11					6517
12					

RISERS LENGHT mm

	A	B	C	
	470	470	470	STANDARD
	340	380	470	ACCELERATED

10.9 DIMENSIONS HOOK 5 P 28

LINES HEIGHT mm

	A	B	C	D	br
1	6980	6865	6933	7060	7672
2	6930	6806	6879	7011	7447
3	6897	6853	6952	7075	7361
4	6811	6713	6794	6903	7297
5	6744	6649	6721		7113
6	6592	6551	6631		7039
7	6499	6512	6611		7087
8	6434	6511	6632		7042
9	6161	6142	6112		6900
10	6029	6033			6779
11					6761
12					

RISERS LENGHT mm

	A	B	C	
	470	470	470	STANDARD
	340	380	470	ACCELERATED

